





## Features and Benefits

### Ease of Maintenance

- Low restriction check valve eliminates loss of prime when draining or changing the filter
- Sturdy, quick-acting drain for water and contaminant removal
- Optional Water-In-Fuel (WIF) sensor available

### High Performance

- Meets OEM efficiency requirements
- 67% increased media area to ensure greater protection of your engine
- 500+ hour service life recommendation
- Proprietary media ensures the best fuel filtration and water separation available

<b>SHORT SINGLE</b> #881050DAV-05	<b>TALL SINGLE</b> #891050DAV-05	<b>SHORT DUPLEX</b> #882050DAV-05	<b>TALL DUPLEX</b> #892050DAV-05
			
<b>Applications</b> Diesel engines with flow rates up to 360 Gal/hr (1363 L/hr)	<b>Applications</b> Diesel engines with flow rates up to 540 Gal/hr (2045 L/hr)	<b>Applications</b> Diesel engines with flow rates up to 720 Gal/hr (2725 L/hr)	<b>Applications</b> Diesel engines with flow rates up to 1080 Gal/hr (4088 L/hr)
<b>Specifications</b> Height: 19.2" (488 mm) Depth: 8.8" (222 mm) Width: 8.2" (208 mm) Weight (dry): 31 lb (14.1 kg) Fuel Capacity*: 1.2 gal (4.6 L) *(w/o filter)	<b>Specifications</b> Height: 26.7" (678 mm) Depth: 8.8" (222 mm) Width: 8.2" (208 mm) Weight (dry): 43 lb (19.5 kg) Fuel Capacity*: 2.5 gal (9.3 L) *(w/o filter)	<b>Specifications</b> Height: 24.7" (617 mm) Depth: 11.1" (282 mm) Width: 26" (660 mm) Weight (dry): 80 lb (36.3 kg) Fuel Capacity*: 2.4 gal (9.2 L)	<b>Specifications</b> Height: 32.2" (808 mm) Depth: 11.1" (282 mm) Width: 26" (660 mm) Weight (dry): 103 lb (46.7 kg) Fuel Capacity*: 4.9 gal (18.6 L)