

### Features and Benefits

#### Ease of Maintenance

- "SEEING IS BELIEVING<sup>®</sup>" technology – see when NOT to change the filter
- Clear bottom bowl with sturdy drain
- Low restriction check valve eliminates loss of prime when draining or changing the filter
- Robust, quick-acting drain for water and contaminant removal

#### Options

- Water-In-Fuel (WIF) sensor
- Electric Heater

#### High Performance

- Meets OEM efficiency requirements
- 67% increased media area to ensure greater protection of your engine
- 500+ hour service life recommendation
- Proprietary media ensures the best fuel/water separation available

### Industrial Pro Engine Displacement Compatibility Matrix

| Engine Displacement in Liters | Fuel Flow Rate Gal/hr (L/hr) | Short Single | Tall Single | Short Duplex | Tall Dual/Duplex | Tall Triple |
|-------------------------------|------------------------------|--------------|-------------|--------------|------------------|-------------|
| 5-19                          | 40-100 (151-378)             | X            |             | X            |                  |             |
| 20-38                         | 101-153 (382-479)            | X            |             | X            |                  |             |
| 39-50                         | 154-206 (583-780)            |              | X           |              | X                | X           |
| 51-60                         | 207-264 (784-1000)           |              | X           |              | X                | X           |

#### SHORT SINGLE



#### Applications

Diesel engines with flow rates up to 300 Gal/hr (1136 L/hr)

#### Specifications

Height: 20" (508 mm)  
 Depth: 12" (305 mm)  
 Width: 11.2" (284 mm)  
 Weight (dry): 29 lb (13 kg)  
 Fuel Capacity (w/o filter): 1.1 gal (4.3 L)

#### SHORT DUPLEX



#### Applications

Diesel engines with flow rates up to 300 Gal/hr (1136 L/hr)

#### Specifications

Height: 20.2" (513 mm)  
 Depth: 12.3" (312 mm)  
 Width: 32" (813 mm)  
 Weight (dry): 58 lb (26.3 kg)  
 Fuel Capacity (w/o filter): 2.5 gal (8.3 L)

#### TALL SINGLE



#### Applications

Diesel engines with flow rates up to 600 Gal/hr (2271 L/hr)

#### Specifications

Height: 28" (711 mm)  
 Depth: 12" (305 mm)  
 Width: 13.9" (352 mm)  
 Weight (dry): 39 lb (17.7 kg)  
 Fuel Capacity (w/o filter): 2.5 gal (9.5 L)

#### TALL DUAL



#### Applications

Flow rates up to 1200 Gal/hr (4543 L/hr)

#### Specifications

Height: 28" (711 mm)  
 Depth: 12" (305 mm)  
 Width: 23.8" (604 mm)  
 Weight (dry): 90 lb (40.8 kg)  
 Fuel Capacity (w/o filter): 5.0 gal (18.9 L)

#### TALL DUPLEX



#### Applications

Flow rates up to 1200 Gal/hr (4543 L/hr)

#### Specifications

Height: 28" (711 mm)  
 Depth: 12" (305 mm)  
 Width: 23.8" (604 mm)  
 Weight (dry): 112 lb (50.8 kg)  
 Fuel Capacity (w/o filter): 5.0 gal (18.9 L)

#### TALL TRIPLE



#### Applications

Flow rates up to 1800 Gal/hr (6813 L/hr)

#### Specifications

Height: 28" (711 mm)  
 Depth: 12" (305 mm)  
 Width: 35" (900 mm)  
 Weight (dry): 135 lb (61.2 kg)  
 Fuel Capacity (w/o filter): 7.5 gal (54.9 L)



A Clariance Technologies Company

DAVCO Technology, LLC

1600 Woodland Drive, Saline, MI 48176-1629

800-328-2611

customerservice@davco.com

www.davco.com