

## Features and Benefits

### Ease of Maintenance

- Seeing is Believing® technology – see when NOT to change the filter
- Clear bottom bowl with sturdy drain
- Low restriction check valve eliminates loss of prime when draining or changing the filter
- Robust, quick-acting drain for water and contaminant removal

### High Performance

- Meets OEM efficiency requirements
- 67% increased media area to ensure greater protection of your engine
- 500+ hour service life recommendation
- Proprietary media ensures the best fuel filtration and water separation available

### Options

- Water-In-Fuel (WIF) sensor
- Electric heater

#### SHORT SINGLE



#### Applications

Diesel engines with flow rates up to 300 Gal/hr (1,136 L/hr)

#### Specifications

|                             |         |          |
|-----------------------------|---------|----------|
| Height:                     | 20"     | (508 mm) |
| Depth:                      | 12"     | (305 mm) |
| Width:                      | 11.2"   | (284 mm) |
| Weight (dry):               | 29 lb   | (13 kg)  |
| Fuel Capacity (w/o filter): | 1.1 gal | (4.3 L)  |

#### SHORT DUPLEX



#### Applications

Diesel engines with flow rates up to 600 Gal/hr (1,136 L/hr) in dual mode

#### Specifications

|                             |         |           |
|-----------------------------|---------|-----------|
| Height:                     | 20.2"   | (513 mm)  |
| Depth:                      | 12.3"   | (312 mm)  |
| Width:                      | 32"     | (813 mm)  |
| Weight (dry):               | 58 lb   | (26.3 kg) |
| Fuel Capacity (w/o filter): | 2.5 gal | (8.3 L)   |

#### TALL SINGLE



#### Applications

Diesel engines with flow rates up to 600 Gal/hr (2,271 L/hr)

#### Specifications

|                             |         |           |
|-----------------------------|---------|-----------|
| Height:                     | 28"     | (711 mm)  |
| Depth:                      | 12"     | (305 mm)  |
| Width:                      | 13.9"   | (352 mm)  |
| Weight (dry):               | 39 lb   | (17.7 kg) |
| Fuel Capacity (w/o filter): | 2.5 gal | (9.5 L)   |

#### TALL DUAL



#### Applications

Flow rates up to 1200 Gal/hr (4543 L/hr) in dual mode

#### Specifications

|                             |         |           |
|-----------------------------|---------|-----------|
| Height:                     | 28"     | (711 mm)  |
| Depth:                      | 12"     | (305 mm)  |
| Width:                      | 23.8"   | (604 mm)  |
| Weight (dry):               | 90 lb   | (40.8 kg) |
| Fuel Capacity (w/o filter): | 5.0 gal | (18.9 L)  |

#### TALL DUPLEX



#### Applications

Flow rates up to 1200 Gal/hr (4543 L/hr) in dual mode

#### Specifications

|                             |         |           |
|-----------------------------|---------|-----------|
| Height:                     | 28"     | (711 mm)  |
| Depth:                      | 12"     | (305 mm)  |
| Width:                      | 23.8"   | (604 mm)  |
| Weight (dry):               | 112 lb  | (50.8 kg) |
| Fuel Capacity (w/o filter): | 5.0 gal | (18.9 L)  |

#### TALL TRIPLE



#### Applications

Flow rates up to 1800 Gal/hr (6813 L/hr) in triple mode

#### Specifications

|                             |         |           |
|-----------------------------|---------|-----------|
| Height:                     | 28"     | (711 mm)  |
| Depth:                      | 12"     | (305 mm)  |
| Width:                      | 35"     | (900 mm)  |
| Weight (dry):               | 135 lb  | (61.2 kg) |
| Fuel Capacity (w/o filter): | 7.5 gal | (54.9 L)  |